

Gfp Machine Overview

WIDE FORMAT LAMINATORS
RUGGED DESIGN
PROFESSIONAL QUALITY
PROVEN PERFORMANCE
ECONOMICALLY PRICED



| | 865DH-4RS | 663TH | 563TH-4RS | 363-TH | 355-TH |
|-----------------------------|------------------------------|------------------------------|------------------------------|-----------------|-----------------|
| Heat / Cold | Dual Heat | Top Heat Assist | Top Heat Assist | Top Heat Assist | |
| Laminating Width | 65" | 63" | 63" | 63" | 55" |
| Maximum Speed (feet/minute) | 13 | 20 | 20 | 20 | |
| Speed Control | Variable | Variable | Variable | Variable | |
| Maximum Temperature | 266° F | 140°F | 140°F | 140°F | |
| Heating Method | Quartz Tube | Metal Alloy | Metal Alloy | Metal Alloy | |
| Mounting Gap | 1" | 1" | 1" | 1" | |
| Pressure/Gap Adjustment | Infinite | Infinite | Infinite | Infinite | |
| Pressure/Gap Mechanism | Dual Hand Wheel | Electric | Hand Wheel | Hand Wheel | |
| Roller Diameter | 5" | 5" | 4.5" | 5" | |
| Main Rollers | Silicone | Silicone | Silicone | Rubber | |
| Supply Shaft | Swing Out with 3" Quick Grip | Swing Out with 3" Quick Grip | Swing Out with 3" Quick Grip | 3" Quick Grip | |
| Tension Adjustment | Single Knob | Single Knob | Single Knob | Single Knob | |
| Film Tension Sensor | - | ✓ | - | - | |
| Digital Microcontroller | - | ✓ | - | - | |
| Color Graphic Display | - | ✓ | - | - | |
| Touchscreen Interface | - | ✓ | - | - | |
| Operating Tutorials | - | ✓ | - | - | |
| Roll Label Printer | - | ✓ | - | - | |
| Web Clutch | ✓ | - | - | - | |
| Motorized Liner & Rewind | ✓ | ✓ | ✓ | Chain Link | |
| Roll to Roll Capable | ✓ | ✓ | ✓ | ✓ | |
| Rear Rewind | ✓ | ✓ | ✓ | ✓ | |
| Inline Slitting | ✓ | ✓ | ✓ | - | |
| Front Unwind | 2 | ✓ | ✓ | ✓ | |
| Foot Pedal | ✓ | ✓ | ✓ | ✓ | |
| Optical Safety Eyes | ✓ | ✓ | ✓ | ✓ | |
| Stand | ✓ | ✓ | ✓ | ✓ | |
| Swing Up Feed Table | ✓ | ✓ | ✓ | ✓ | |
| Power Supply | 240v 24A | 120v 12A | 110v 12A | 120v 12a | 120v 11a |
| Power Consumption | 5760W | 1440W | 1320W | 1440W | 1320W |
| Warranty Parts | 1 year | 1 year | 1 year | 1 year | |
| Warranty Labor | 1 year | 1 year | 1 year | 1 year | |
| Installation & Training | Included | Optional | Optional | Optional | |
| Net Weight (LBS.) | 846 | 675 | 491 | 376 | 321 |
| Dimensions | 87" x 34" x 49" | 83" x 31" x 63" | 87" x 26.5" x 52.5" | 80" x 23" x 48" | 72" x 23" x 48" |
| Safety Approval | cTUVus | cTUVus | cTUVus | cTUVus | cTUVus |

Gfp Machine Overview

WIDE FORMAT LAMINATORS
RUGGED DESIGN
PROFESSIONAL QUALITY
PROVEN PERFORMANCE
ECONOMICALLY PRICED



| | 263-C | 255-C | 230-C | 220-C | FT48 |
|-----------------------------|-----------------|-----------------|-----------------|---------------------------|-----------------|
| Heat / Cold | Cold | | Cold | Cold | - |
| Laminating Width | 63" | 55" | 30" | 20" | - |
| Maximum Speed (feet/minute) | 13 | | 11.5 | 11.5 | - |
| Speed Control | Variable | | Variable | Variable | - |
| Maximum Temperature | - | | - | - | - |
| Heating Method | - | | - | - | - |
| Mounting Gap | 1" | | 1/2" | 1/2" | - |
| Pressure/Gap Adjustment | Infinite | | Infinite | Infinite | - |
| Pressure/Gap Mechanism | Hand Wheel | | Hand Wheel | Hand Wheel | - |
| Roller Diameter | 4.5" | | 2.5" | 2.5" | - |
| Main Rollers | Rubber | | Rubber | Rubber | - |
| Supply Shaft | 3" Quick Grip | | 3" Quick Grip | 3" Quick Grip | - |
| Tension Adjustment | Single Knob | | Single Knob | Single Knob | - |
| Film Tension Sensor | - | | - | - | - |
| Digital Microcontroller | - | | - | - | - |
| Color Graphic Display | - | | - | - | - |
| Touchscreen Interface | - | | - | - | - |
| Operating Tutorials | - | | - | - | - |
| Roll Label Printer | - | | - | - | - |
| Web Clutch | - | | - | - | - |
| Motorized Liner & Rewind | Chain Link | | ✓ | ✓ | - |
| Roll to Roll Capable | - | | - | - | - |
| Rear Rewind | - | | - | - | - |
| Inline Slitting | - | | - | - | - |
| Front Unwind | ✓ | | ✓ | ✓ | - |
| Foot Pedal | ✓ | | ✓ | ✓ | - |
| Optical Safety Eyes | ✓ | | ✓ | ✓ | - |
| Stand | ✓ | | ✓ | Optional | - |
| Swing Up Feed Table | Fixed | | ✓ | ✓ | - |
| Power Supply | 110v 0.4A | | 110v 0.4A | 110v 0.3A | - |
| Power Consumption | 44W | | 33W | 33W | - |
| Warranty Parts | 1 year | | 1 year | 1 year | 1 year |
| Warranty Labor | 1 year | | 1 year | 1 year | 1 year |
| Installation & Training | Optional | | Optional | Optional | Optional |
| Net Weight (LBS.) | 322 | 257 | 120 | 113 | 148 |
| Dimensions | 80" x 24" x 55" | 73" x 24" x 55" | 43" x 17" x 42" | 16" x 22" x 38" w/o stand | 71" x 49" x 38" |
| Safety Approval | cTUVus | cTUVus | cTUVus | cTUVus | - |